

PASSIVE TEMPERATURE SENSORS PTE-OI

Outside air temperature/illuminance sensor for HVAC applications



PTE-OI is a combination of a passive temperature and an illuminance sensor engineered for HVAC applications. PTE-OI is used to sense outside air temperature and ambient lighting conditions. The temperature sensor is housed inside a stainless steel sleeve that protects it from the environment and condensation, ensuring long service life. In addition to the outside air temperature, the PTE-OI includes an ambient illuminance sensor. The illuminance sensor is hermetically sealed for protection.

PTE-OI is available with the following sensor types:

- NTC10k
- NTC20k
- Pt1000
- Ni1000
- Ni1000-LG



APPLICATIONS

PTE-OI is commonly used in HVAC systems for:

- measuring outside air temperature
- controlling the outside lighting of buildings

MODEL SUMMARY

Description	Model	Product code
Passive temperature sensor - outside with illuminance		
- with NTC10k sensor	PTE-OI-NTC10	505.011.101
- with NTC20k sensor	PTE-OI-NTC20	505.012.101
- with Pt1000 sensor	PTE-OI-Pt1000	505.013.101
- with Ni1000 sensor	PTE-OI-Ni1000	505.014.101
- with Ni1000-LG sensor	PTE-OI-Ni1000-LG	505.015.101

PASSIVE TEMPERATURE SENSORS PTE-01

SPECIFICATIONS

Performance

Illuminance

measurement range:

0...1000 lx

Accuracy:

NTC10k

 \pm 0.25 °C @ 25 °C

NTC20k

± 0.25 °C @ 25 °C

Pt1000

± 0.3 °C @ 0 °C

Ni1000

 \pm 0.4 °C @ 0 °C

Ni1000-LG

± 0.4 °C @ 0 °C

Illuminance sensor

± 20 % @ 100 lx

Protection class:

IP54

Technical Specifications

Environment:

Operating temperature:

-50 ... +50 °C

Physical

Housing material:

ABS

Cover material:

PMMA

Housing dimensions:

90.0 x 95.0 x 36.0 mm

Weight:

95 g

Conformance

Meets the requirements for CE marking: RoHS Directive 2011/65/EU WEEE Directive 2012/19/EU

COMPANY WITH MANAGEMENT SYSTEM **CERTIFIED BY DNV GL**

= ISO 9001 = ISO 14001 =





HOW TO GENERATE A MODEL?

Example:	Product series	Product series				
PTE-OI-NTC10	PTE	Passive t	emperature senso	or for gas		
		Installati	on type			
		-Cable	Cable			
		-Duct	Duct			
		-Room	Room			
		-0	Outside			
		-01	Outside with III	luminance		
			Sensor elemen	ut .		
			-NTC10	10 kΩ @ 25 °C		
			-NTC20	20 kΩ @ 25 °C		
			-Pt1000	1000 Ω @ 0 °C		
			-Ni1000	1000 Ω @ 0 °C		
			-Ni1000-LG	1000 Ω @ 0 °C		
Model	PTE	-01	-NTC10			